



Overview

**HP recommends Windows Vista®
Business**



- | | |
|---|--|
| 1. Volume mute button with LED indicator | 12. Hard drive activity / HP 3D DriveGuard LED |
| 2. Volume scroll zone with up/down LED indicators | 13. Battery charging LED |
| 3. Integrated microphone | 14. Power/standby LED |
| 4. RJ-11/modem port | 15. Wireless on/off LED |
| 5. Optical drive | 16. Power button with LED |
| 6. Media Card Reader | 17. HP Info / HP QuickLook button with LED indicator |
| 7. 2 USB 2.0 ports | 18. Wireless on/off button with LED indicator |
| 8. HP Fingerprint Sensor | 19. HP Presentation button with LED indicator |
| 9. Integrated stereo speakers | 20. WLAN antennas (with WLAN option) |
| 10. Touchpad with scroll zone | 21. WWAN antennas (with WWAN option) |
| 11. Touchpad buttons | |

Overview



- | | |
|------------------------------|-----------------------------------|
| 1. Power connector | 7. PC Card eject button |
| 2. 2 USB 2.0 ports | 8. S-Video TV out |
| 3. Stereo headphone/line out | 9. VGA/external monitor connector |
| 4. Stereo microphone in | 10. RJ-45/Ethernet port |
| 5. 1394a port | 11. Kensington Lock slot |
| 6. Type I/II PC Card slot | |

At A Glance

- Genuine Windows Vista Business*, Genuine Windows Vista Home Basic, Genuine Windows XP Professional, or FreeDOS
- Widescreen 15.4-inch diagonal display with wide-viewing angle, BrightView and HP Privacy Filter support
- Flexible wireless connectivity options:
 - Integrated HP ev2200 1xEV-DO or HP hs2300 HSDPA Broadband Wireless module
 - Integrated 802.11 a/b/g/draft-n, a/b/g, or b/g wireless LAN module
 - Bluetooth®
- Designed for common image for corporate environments
- AMD Turion™ 64 X2 Dual-Core Mobile Technology, AMD Athlon™ 64 X2 Dual-Core Processors for Notebook PCs, or Mobile AMD Sempron™ processors
- Thin, lightweight design starting at 5.7 lb/2.59 kg and 1.37 in/34.9 mm thin at front
- Security features including Drive Encryption for HP ProtectTools, HP Fingerprint Sensor, TPM 1.2**
- HP QuickLook on Windows Vista models for instant access to email, calendar, and contact information
- Up to 250-GB 5400 rpm or 120-GB 7200 rpm user-removable hard drive with HP 3D DriveGuard protection
- Media Card Reader
- Touch-sensitive controls for HP Info Center, HP QuickLook, wireless on/off, HP Presentation button, external volume up, volume down, and mute
- Integrated optical drive, including optional DVD+/-RW SuperMulti DL LightScribe Drive
- Up to 4 GB of 667-MHz DDR2 SDRAM, dual channel memory support
- ATI Radeon X1250 graphics, with up to 831 MB shared system memory (select models)
- Broadcom NetLink Gigabit Ethernet Controller
- Touchpad with scroll zone

* At initial boot, either 32- or 64-bit can be selected. This is a one time selection and the other version will be deleted.

** TPM module disabled where not permitted by law (for example, Russia and China).

Standard Features

Processors

AMD Turion 64 X2 Dual-Core Mobile Technology TL-66 (2.3-GHz, 2 x 512-KB L2 cache)
AMD Turion 64 X2 Dual-Core Mobile Technology TL-64 (2.2-GHz, 2 x 512-KB L2 cache)
AMD Turion 64 X2 Dual-Core Mobile Technology TL-62 (2.1-GHz, 2 x 512-KB L2 cache)
AMD Turion 64 X2 Dual-Core Mobile Technology TL-60 (2.0-GHz, 2 x 512-KB L2 cache)
AMD Turion 64 X2 Dual-Core Mobile Technology TL-58 (1.9-GHz, 2 x 512-KB L2 cache)
AMD Turion 64 X2 Dual-Core Mobile Technology TL-56 (1.8-GHz, 2 x 512-KB L2 cache)
AMD Turion 64 X2 Dual-Core Mobile Technology TL-52 (1.6-GHz, 2 x 512-KB L2 cache)
AMD Turion 64 X2 Dual-Core Mobile Technology TL-50 (1.6-GHz, 2 x 256-KB L2 cache)
AMD Turion 64 Mobile Processor MK-38 (2.2-GHz, 512-KB L2 cache)
AMD Athlon 64 X2 Dual-Core Processor for Notebook PCs TK-53 (1.7-GHz, 2 x 256-KB L2 cache)
Mobile AMD Sempron Processor 4000+ (2.2-GHz, 512-KB L2 cache)
Mobile AMD Sempron Processor 3800+ (2.2-GHz, 256-KB L2 cache)
Mobile AMD Sempron Processor 3600+ (2.0-GHz, 256-KB L2 cache)
Mobile AMD Sempron Processor 3500+ (1.8-GHz, 512-KB L2 cache)
Mobile AMD Sempron Processor 3400+ (1.8-GHz, 256-KB L2 cache)

NOTE: Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

Operating System

Preinstalled

Genuine Windows Vista Business^{†*}
Genuine Windows Vista Home Basic*
Genuine Windows XP Professional
FreeDOS

Supported

Genuine Windows Vista Enterprise*

Certified

SuSE Linux Enterprise Desktop 10

[†] At initial boot, either 32- or 64-bit can be selected. This is a one time selection and the other version will be deleted.

* Certain Windows Vista product features require advanced or additional hardware. See <http://www.microsoft.com/windowsvista/getready/hardwarereqs.msp> and <http://www.microsoft.com/windowsvista/getready/capable.msp> for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit <http://www.windowsvista.com/upgradeadvisor>.

Chipset

AMD M690T Chipset

Standard Features

Graphics

ATI Radeon X1250

Total System Memory	Reserved Graphics Memory *	Maximum Graphics Memory **
Windows XP		
256 MB	32 MB	32 MB
512 or 768 MB	64 MB	64 MB
1024 MB or more	128 MB	128 MB
Windows Vista		
512 MB	64 MB	128 MB
768 MB	64 MB	159 MB
1024 MB	128 MB	319 MB
1536 MB	128 MB	575 MB
2048 MB	128 MB	831 MB

* System memory exclusive to graphics.
 ** Total available graphics memory (HyperMemory), which includes Reserved Graphics Memory and Shared System Memory.

Microsoft DirectX 9 capable

Display

Internal
 15.4-inch diagonal WXGA anti-glare (1280 x 800 resolution)
 15.4-inch diagonal WXGA BrightView (1280 x 800 resolution)
 15.4-inch diagonal WSXGA+ WVA anti-glare (1680 x 1050 resolution)
 HP Privacy Filter support

External
 Up to 32-bit per pixel color depth
VGA port supports resolutions up to 2048 x 1536 at 75 Hz, and lower resolutions at up to 100 Hz
NOTE: Resolutions are dependent upon monitor capability, and resolution and color depth settings.

Memory

Standard
 512-MB, 1024-MB, 2048-MB, or 4096-MB 667-MHz DDR2 SDRAM; two SODIMM slots supporting dual channel memory

Maximum
 Upgradeable to 4096-MB maximum (2048-MB SODIMM in slots 1 and 2)

Dual-channel
 Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

NOTE: Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed. Full availability of 4 GB of memory requires Windows Vista Business 64-bit or Linux. With Windows 32-bit operating systems, the amount of usable memory is dependent upon your configuration, so that above 3 GB all memory may not be available due to system resource requirements.

Communications

Integrated Broadcom NetLink Gigabit Ethernet Controller (10/100/1000 NIC)*
 56K V.92 modem**

* The term "10/100/1000" or "Gigabit" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

** Designed for downloads from 56K modem compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions. Modem availability is subject to country regulatory approval.



Standard Features

Wireless Devices

Support for a broad range of secure, integrated wireless LAN and wireless WAN options featuring support for the latest industry standards. Broadband Wireless (WWAN) requires Windows Vista Business or Windows XP Professional and is available in select countries. Integrated Bluetooth is also available and can be combined with any of the supported wireless LAN and wireless WAN options. All wireless options are factory configurable only.

HP ev2200 1xEV-DO Broadband Wireless Module

Integrated WWAN module connects to the Verizon Wireless BroadbandAccess and NationalAccess networks (U.S. only). Supports CDMA 1xEV-DO, 1xRTT connections at 850 and 1900 MHz.
NOTE: Separately purchased Verizon Wireless service is required. For details, go to <http://www.hp.com/go/broadbandwireless>.
Two 850/900/1800/1900/2100-MHz antennas integrated in the top of the display panel support current and future WWAN technologies

HP hs2300 HSDPA Broadband Wireless Module

Integrated WWAN module that provides connection to GSM, GPRS, EDGE, UMTS, and HSDPA mobile networks in many countries. Currently available for the AT&T Broadbandconnect network in the U.S. (supports international roaming).
NOTE: Separately purchased mobile network operator service is required.
Two 850/900/1800/1900/2100-MHz antennas integrated in the top of the display panel support current and future WWAN technologies.

All 802.11a/b/g integrated wireless LAN options

Wi-Fi certified
Cisco Compatible Extensions support (Version 4.0) with Microsoft Windows XP
Wired Equivalent Privacy (WEP) support up to 128-bit keys
Wi-Fi Protected Access (WPA) and WPA2 support
802.1x authentication support, including EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, and LEAP
Advanced Encryption Standard (AES) support
WiFi certified for WPA2, WMM
Dual antennas integrated in the display enclosure

Broadcom 4321AGN 802.11a/b/g/draft-n Wi-Fi Adapter

Integrated support for 802.11a, b, g, and draft-n
Up to 300-mbps data rate

Broadcom 4311AG 802.11a/b/g WiFi Adapter

Integrated support for 802.11 a, b and g
Up to 54-mbps data rate

Broadcom 4311BG 802.11b/g WiFi Adapter

Integrated support for 802.11 b and g
Up to 54-mbps data rate

HP Integrated Module with Bluetooth Wireless Technology

Bluetooth Specification v2.0 compliant
Works with a wide range of Bluetooth devices

Keyboard

The 101/102-key compatible keyboard features an industry standard, full-pitch key layout with desktop keyboard features, such as the isolated inverted-T cursor control keys, editing keys, both left and right control and alt keys, and 12 function keys. US and International key layouts are available. Other features include an integrated numeric keypad, hotkeys for instant access to power conservation, brightness, and other features, 19-mm x 19-mm key pitch (center-to-center spacing), 2.5-mm stroke, and comfort-dished keycaps.

Standard Features

Touch-sensitive controls Touch-sensitive controls provide easy access to the following features: HP Info Center, HP QuickLook, wireless on/off, HP Presentation button, external volume up, volume down, and mute

Pointing device Touchpad with scroll zone, two pick buttons

Expansion card slots **1 Type I/II PC Card slot** Supports 32-bit CardBus and 16-bit PC Cards
or
Optional Integrated Smart Card Reader Compatible with ISO 7816 compliant Smart Cards
 PC/SC interface support
 (replaces PC Card slot)
Media Card Reader Supports SD (Secure Digital), MMC (MultiMedia Card), Memory Stick, Memory Stick Pro, Memory Stick Duo*, xD-Picture card
 *NOTE: Memory Stick Duo Adapters are required and sold separately. Inserting a Memory Stick Duo Card directly into your notebook could damage the memory card and/or notebook.

Storage

Hard drives 80/120/160/250-GB 5400 rpm SMART SATA
 80/120-GB 7200 rpm SMART SATA

NOTE: These hard drives are customer removable and will withstand multiple insertion/removal cycles. Up to 10 GB is reserved for the system recovery software.

HP 3D DriveGuard The hard drive is mounted directly to the notebook frame, reducing the transmission of shock to the hard drive. Uses three-axis digital motion detection with intelligent sensitivity to help protect the hard drive during normal use from shock and vibration. The digital accelerometer temporarily halts all data transfer and parks the hard drive when abrupt motion is detected.

Fixed optical drives DVD-ROM Drive
 DVD/CD-RW Combo Drive
 DVD+/-RW SuperMulti DL Drive
 DVD+/-RW SuperMulti DL LightScribe Drive

Interfaces

PC Card slot One Type I/II PC Card slot or optional Smart Card Reader

External monitor One – VGA

1394a One

Stereo microphone in One

Stereo headphone/line out One

Power connector One

RJ-11/modem One

RJ-45/Ethernet One

S-video TV out One (Support for NTSC/PAL)

USB 2.0 Four

Docking connector One

Secondary battery connector One

LED status indicators Fifteen

Standard Features

Audio	High Definition Audio support w/24-bit DAC Integrated stereo speakers Integrated microphone Touch-sensitive controls for volume up, volume down, and mute Stereo headphone/line out Stereo microphone in
Software	Preinstalled software with Windows Vista or Windows XP PDF Complete HP Backup and Recovery Manager HP Help and Support Center HP QuickLook (Windows Vista only) HP OpenView Radia Management Agent HP Universal Print Driver HP ProtectTools Security Manager: BIOS Configuration for HP ProtectTools Credential Manager for HP ProtectTools Device Access Manager for HP ProtectTools* Drive Encryption for HP ProtectTools Embedded Security for HP ProtectTools HP Quick Launch Buttons HP Wireless Assistant Microsoft Office Ready with 60-day Office Professional 2007 Trial Edition (select models) Roxio Creator 9 (for optional DVD+/-RW and DVD/CDRW drives) Synaptics Touchpad Driver Symantec Norton Internet Security with complimentary 60-day live update Intervideo WinDVD – DVD Player Additional software available from the web HP Client Manager Java Card Security for HP ProtectTools <i>* Download available from http://www.hp.com for Windows Vista; preinstalled with Windows XP.</i>

HP Backup and Recovery Manager	Each unit is shipped with HP Backup and Recovery Manager. HP Backup and Recovery Manager can provide data and system file protection for HP business PCs to enable fast recovery if the system becomes corrupted or if important information is accidentally deleted. HP Backup and Recovery Manager can perform scheduled or manual backups of the entire drive or individual files and folders. Up to 10 GB of the hard drive is reserved for the system recovery software. HP Backup and Recovery Manager can also create software recovery CDs or DVDs (requires optional hardware).
---------------------------------------	--

SMBIOS Version 2.4	System Management BIOS, previously known as DMI BIOS, is used to store system management information.
---------------------------	---

Standard Features

HP ProtectTools Security Manager

HP ProtectTools Security Manager is the security platform for business notebooks and desktops. The HP ProtectTools Security Manager is an extensible client security console that delivers enhanced security capabilities through add-on software modules. Modules currently available are:

- BIOS Configuration for HP ProtectTools
- Credential Manager for HP ProtectTools
- Device Access Manager for HP ProtectTools
- Drive Encryption for HP ProtectTools
- Embedded Security for HP ProtectTools
- Java Card Security for HP ProtectTools

Security

Standard Features

HP ProtectTools Security Manager
 HP Fingerprint Sensor
 Configuration Control Hardware
 Memory Change Alert
 Ownership Tag
 Setup Password
 Power-On Password
 TPM 1.2 Embedded Security Chip*
 TPM Enhanced DriveLock*
 HP Disk Sanitizer
 HP 3D DriveGuard
 Kensington Lock Slot
 Support for Computrace / LoJack for Laptops (must be purchased separately)

Optional Features

Smart Card Reader Compatible with ISO 7816 compliant Smart Cards
 (replaces Type I/II PC Card slot) PC/SC interface support

HP Privacy Filter Narrows viewing area so that screen data is visible only to persons directly in front of the monitor

***NOTE:** TPM module disabled where use is restricted by law; for example, Russia and China. For more information on HP security solutions refer to <http://www.hp.com/go/security>.

Power Supply

External 90-watt Smart AC adapter, 6-foot (1.8-meter) power cord included.
 Total length including external AC adapter is 12 feet (3.66 meter).
 HP Fast Charge*

*HP Fast Charge recharges your battery up to 90% within 90 minutes when the system is off. HP Fast Charge does not apply to 12-cell Ultra-Capacity batteries.

Battery

Primary battery

6-cell (55 WHr) Lithium-Ion battery
 6-cell (47 WHr) Lithium-Ion battery

Optional HP Extended Life Battery

8-cell (52 WHr) high capacity Lithium-Ion battery

Optional HP Ultra-Capacity Battery

12-cell (95 WHr) high capacity Lithium-Ion battery

Standard Features

Battery Life

	6-cell (55 WHr) Primary	6-cell (47 WHr) Primary
Primary battery	Up to 4 hours and 30 minutes	Up to 3 hours and 45 minutes
Primary battery and optional HP Extended Life Battery	Up to 8 hours and 30 minutes	Up to 8 hours
Primary battery and optional HP Ultra-Capacity Battery	Up to 12 hours	Up to 11 hours and 15 minutes

NOTE: The listed battery life measurements were taken on models running Microsoft Windows XP Professional. Battery life will vary depending on the product configuration, product model, applications loaded on the product, power management settings of the product, and the product features used by the customer. As with all batteries, the maximum capacity of this battery will decrease with time and usage.

System Standby Time Up to 1 week

Power Conservation ATI PowerPlay technology
Hibernation
Standby
ACPI compliance

Docking and Stands HP Advanced Docking Station
HP Docking Station
HP Standard Monitor Stand
HP Adjustable Notebook Stand
HP External MultiBay II

HP's shared docking solutions provide simple and convenient port replication and cable management. Features include Gigabit NIC pass through, modem pass through, legacy parallel and serial ports, S-video TV out, USB 2.0 ports, integrated security mechanism*, integrated MultiBay II and ExpressCard** slots. These docking solutions are compatible across multiple Business Notebook platforms enabling a lower total cost of ownership.

* HP/Kensington Cable Lock required (purchased separately)

** HP 3-in-1 NAS Docking Station and HP Advanced Docking Station only

Service and Support HP Services offers limited 3- year, 1-year and 90-day warranty options depending on country; 1-year limited warranty on primary battery. On-site service and warranty upgrades are also available. For HP Care Pack services see <http://www.hp.com/go/lookuptool>.

NOTE: Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details.

<http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp>.

Options

Memory	HP 512-MB (DDR2 667 MHz) SODIMM	EM993AA
	HP 1-GB (DDR2 667 MHz) SODIMM	EM994AA
	HP 2-GB (DDR2 667 MHz) SODIMM	EM995AA
MultiBay II Storage (9.5-mm) NOTE: Requires HP 3-in-1 NAS Docking Station, HP Advanced Docking Station, or HP External MultiBay II	HP MultiBay II DVD-ROM Drive	PA849A
	HP MultiBay II DVD/CD-RW Combo Drive	PA850A
	HP MultiBay II DVD+/-RW SuperMulti DL Drive	PA851A
	HP 80-GB 5400rpm MultiBay II Hard Drive	PH357A
Other Storage	HP 80-GB 5400rpm Primary SATA Hard Drive	ET354AA
	HP DVD+/-RW SuperMulti DL LightScribe Drive	ET353AA
	HP Notebooks USB Diskette Drive	DC361B
Expansion Solutions	HP Docking Station with Smart Adapter	EN488AA#xxx
	HP Advanced Docking Station with Smart Adapter	EN489AA#xxx
	HP Standard Monitor Stand	PA507A
	HP Adjustable Notebook Stand	PA508A
	HP External MultiBay II	PA509A#xxx
Power	HP 2-Bay Battery Charging Station (North America only)	DT533A#xxx
	HP 2-Bay Battery Charging Station (rest of world)	EW424AA#xxx
	HP 10-Bay Battery Charging Station (North America only)	DT534A#ABA
	HP Battery Adapter Kit	PK402A
	HP 90W Smart AC Adapter	ED495AA#xxx
	HP 90W Smart Auto Adapter	ED493AA
	HP 65W AC/Auto/Air Combo Smart Adapter	ED993AA#xxx
	HP 6-Cell Li-Ion Primary Battery	PB994A
	HP 8-cell Extended Life Battery	PB993A
HP 12-cell Ultra-Capacity Battery	EJ092AA	
Carrying Cases	HP Value Nylon Case	RR314AA
	HP Universal Nylon Case	RR315AA
	HP Executive Leather Case	RR316AA
	HP Deluxe Nylon Backpack	RR317AA
	HP Universal Messenger Bag	GD404AA
	HP Deluxe Roller Case	GD405AA

Options

Security	HP PC Card Smart Card Reader with Java Card	EL347AA
	HP ProtectTools Java Card – 10 units	EL348AA
	HP/Kensington MicroSaver Security Lock	PC766A
<hr/>		
Input/Output Devices	HP PS/2 Keyboard & Mouse Bundle	RC464AA#xxx
	HP USB Keyboard & Mouse Bundle	RC465AA#xxx
	HP USB/PS2 Optical 2-Button Scroll Mouse	DC369A
	HP USB Optical Travel Mouse	RH304AA
	HP Bluetooth PC Card Mouse	RJ316AA

Memory

Support for up to 4096 MB of 667-MHz DDR2 SDRAM
 Two DIMM slots
 DIMM sizes supported: 512 MB, 1024 MB, and 2048 MB

- Standard Memory**
- 512 MB (512 MB x 1)
 - 1024 MB (1024 MB x 1 or 512 MB x 2)
 - 2048 MB (2048 MB x 1 or 1024 MB x 2)
 - 4096 MB (2048 MB x 2)

Optional Memory Upgrades Support for up to 4096 MB of memory is available (with the installation of optional DDR2 SDRAM memory kits). Both memory slots are user accessible. Please refer to the Hardware and Software Guide for installation procedures. Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

Up to	Slot 1	Slot 2
1024 MB	1024 MB	Empty
1024 MB	512 MB	512 MB
1536 MB	1024 MB	512 MB
2048 MB	1024 MB	1024 MB
4096 MB	2048 MB	2048 MB

NOTE: This chart does not represent all possible memory configurations. Due to the non-industry standard nature of some third-party memory modules, we strongly recommend using only HP branded memory modules to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed. Full availability of 4 GB of memory requires Windows Vista Business 64-bit or Linux. With Windows 32-bit operating systems, the amount of usable memory is dependent upon your configuration, so that above 3 GB all memory may not be available due to system resource requirements.

Memory Upgrades	HP 512-MB (DDR2 667 MHz) SODIMM	EM993AA
	HP 1024-MB (DDR2 667 MHz) SODIMM	EM994AA
	HP 2048-MB (DDR2 667 MHz) SODIMM	EM995AA

Storage

Removable Media Drive Support

	Quantity Supported	Drive Bay
DVD-ROM Drive	One	Fixed optical drive bay
DVD/CD-RW Combo Drive	One	Fixed optical drive bay
DVD+/-RW SuperMulti DL Drive	One	Fixed optical drive bay
DVD+/-RW SuperMulti DL LightScribe Drive	One	Fixed optical drive bay

Hard Drive Support

	Quantity Supported	Drive Bay
Primary Hard Drives		
250-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
160-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
120-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
80-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
120-GB 7200 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
80-GB 7200 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay

Technical Specifications

System Unit	Dimensions (HxWxD)	1.37 in (at front) x 14.05 in x 10.43 in 34.9 mm (at front) x 357.0 mm x 265.0 mm
	Weight	Starting from 5.7 lb (2.59 kg)
	NOTE: Height varies depending upon where on the notebook the measurement is made. Weight varies by configuration and components. Weight includes 6-cell battery, 80-GB hard drive, and optical drive. Weight varies by configuration and components.	
	Stand-Alone Power Requirements (AC Power)	Nominal Operating Voltage 18.5 V Average Operating Power 12.5 W Max Operating Power < 90 W
	Temperature	Operating 32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical) Non-operating -4° to 140° F (-20° to 60° C)
	Relative Humidity	Operating 10% to 90%, non-condensing Non-operating 5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
	Shock	Operating 125 G, 2 ms, half-sine Non-operating 200 G, 2 ms, half-sine
	Random Vibration	Operating 0.75 grms Non-operating 1.50 grms
	Altitude (unpressurized)	Operating -50 to 10,000 ft (-15.24 to 3,048 m) Non-operating -50 to 40,000 ft (-15.24 to 12,192 m)
	Industry Standard Certifications	UL Yes CSA Yes FCC Compliance Yes ENERGY STAR® 4.0 Yes ICES Yes GS Yes Australia / NZ A-Tick Compliance Yes CCC Yes Japan VCCI Compliance Yes MIC Yes BSMI Yes CE Marking Compliance Yes BNCI or BELUS Yes CIT Yes GOST Yes Saudi Arabian Compliance (ICCP) Yes SABS Yes UKRSERTCOMPUTER Yes

For accessibility information on HP products, please visit <http://www.hp.com/accessibility>.

Technical Specifications

HP 90W Smart AC Adapter	Dimensions	5.24 x 2.28 x 1.1 in (13.3 x 5.8 x 2.9 cm)	
	Weight	0.86 lb (390 g)	
	Input	Input	100 to 240 VAC
		Input Efficiency	83% min at 115 VAC
		Input frequency range	47 to 63 Hz
	Output	Input AC current	1.5 A at 90 VAC, 0.75 A at 180 VAC PFC Version 2.4 A at 90 VAC, 1.2 A at 180 VAC NON PFC Version
		Output power	90W
		DC output	18.5V
		Hold-up time	5 msec at 115 VAC input
	Connector	Output current limit	<11A, Over voltage protection- 29V max automatic shutdown
		Connector	3 pin/grounded, mates with interchangeable cords
	Environmental Design	Operating temperature	32° to 104° F (0° to 40° C)
		Non-operating (storage) temperature	-4° to 149° F (-20° to 65° C)
		Altitude	0 to 10,000 ft (0 to 3,048 m)
		Humidity	20% to 80%
Storage Humidity		10% to 90%	
EMI and Safety Certifications	CE Mark – full compliance with LVD and EMC directives; Worldwide safety standards – IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals – C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF- over 200,000 hours at 25°C ambient condition.		

Optional HP Ultra-Capacity Battery	Dimensions (H x W x L)	1.3 x 6.0 x 10.6 in (3.33 x 15.25 x 26.88 cm)	
	Weight	1.77 lb (0.803 kg)	
	Cells/Type	12-cell Lithium-Ion	
	Energy	Watt-hour Capacity	95Wh
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (-10° to 60° C)
		Non-operating	-4° to 140° F (-20° to 60° C)
	Battery Re-Charge Time	Smart Adapter	3 to 4 hours
		System ON	4 to 5 hours (depending on system power consumption)
	Fuel Gauge	When pressed, LEDs light indicating level of charge remaining on battery	

Technical Specifications

Optional HP Extended Life Battery	Dimensions (H x W x L)	1.0 x 3.9 x 8.7 in (2.5 x 10.0 x 22.0 cm)		
	Weight	1.00 lb (0.455 kg)		
	Cells/Type	8-cell Lithium-Ion		
	Energy	Watt-hour Capacity	52Wh	
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)	
		Operating (Discharging)	14° to 140° F (-10° to 60° C)	
		Non-operating	-4° to 140° F (-20° to 60° C)	
	Battery Re-Charge Time	System in OFF mode or Standby	3 hours	
		System ON	3 to 5 hours (depending on system power consumption)	
		HP Fast Charge	Charges the battery up to 90% within 90 minutes when system is OFF	
Fuel Gauge	When pressed, LEDs light indicating level of charge remaining on battery			

6-Cell (55Whr) Lithium-Ion battery	Dimensions (H x W x L)	0.8 x 2.1 x 8.0 in (2.0 x 5.3 x 20.3 cm)		
	Weight	0.737 lb (0.335 kg)		
	Cells/Type	6-cell Lithium-Ion		
	Energy	Watt-hour Capacity	55Wh	
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)	
		Operating (Discharging)	14° to 140° F (-10° to 60° C)	
		Non-operating	-4° to 140° F (-20° to 60° C)	
	Battery Re-Charge Time	System in OFF Mode or Standby	2.5 hours	
		System ON	3 to 5 hours (depending on system power consumption)	
		HP Fast Charge	Charges the battery up to 90% within 90 minutes when system is OFF	

6-Cell (47Whr) Lithium-Ion battery	Dimensions (H x W x L)	0.8 x 2.1 x 8.0 in (2.0 x 5.3 x 20.3 cm)		
	Weight	0.715 lb (0.325 kg)		
	Cells/Type	6-cell Lithium-Ion		
	Energy	Watt-hour Capacity	47Wh	
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)	
		Operating (Discharging)	14° to 140° F (-10° to 60° C)	
		Non-operating	-4° to 140° F (-20° to 60° C)	
	Battery Re-Charge Time	System in OFF Mode or Standby	2.5 hours	
		System ON	3 to 5 hours (depending on system power consumption)	
		HP Fast Charge	Charges the battery up to 90% within 90 minutes when system is OFF	

Technical Specifications

15.4-inch WSXGA+ wide-viewing angle, anti-glare	Dimensions (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)
	Diagonal Size	15.4 in (39.1 cm)
	Surface Treatment	Anti-glare
	Contrast Ratio	300:1 (typical)
	Refresh Rate	60 Hz
	Brightness	200 nit (typical)
	Pixel Resolution	Pitch 0.197 mm
		Format 1680 x 1050
		Configuration RGB stripe
	Backlight	CCFL
	PPI	129
Viewing Angle	±60° Horizontal, ± 50° Vertical (minimum)	

15.4-inch WXGA anti-glare	Active Area (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)
	Diagonal Size	15.4 in (39.1 cm)
	Surface Treatment	Anti-glare
	Contrast Ratio	300:1 (typical)
	Refresh Rate	60 Hz
	Brightness	200 nit (typical)
	Pixel Resolution	Pitch 0.259 mm
		Format 1280 x 800
		Configuration RGB stripe
	Backlight	CCFL
	PPI	98
Viewing Angle	±30° Horizontal, ±10° Vertical (minimum)	

15.4-inch WXGA BrightView	Active Area (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)
	Diagonal Size	15.4 in (39.1 cm)
	Surface Treatment	BrightView
	Contrast Ratio	300:1 (typical)
	Refresh Rate	60 Hz
	Brightness	200 nit (typical)
	Pixel Resolution	Pitch 0.259 mm
		Format 1280 x 800
		Configuration RGB stripe
	Backlight	CCFL
	PPI	98
Viewing Angle	±30° Horizontal, ±10° Vertical (minimum)	

Hard Drives



Technical Specifications

120-GB 7200 rpm SATA	Drive Weight	0.25 lb (113 g)	
	Capacity	120 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous	100 MB/s (Drive Capability)
		(maximum)	
	Seek Time	Single Track	1 ms
	(typical reads, including settling)	Average	10 ms
		Maximum	18 ms
	Rotational Speed	7200 rpm	
	Logical Blocks	234,441,648	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

80-GB 7200 rpm SATA	Drive Weight	0.25 lb (113 g)	
	Capacity	80 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous	100 MB/s (Drive Capability)
		(maximum)	
	Seek Time	Single Track	1 ms
	(typical reads, including settling)	Average	10 ms
		Maximum	18 ms
	Rotational Speed	7200 rpm	
	Logical Blocks	156,301,488	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

250-GB 5400 rpm SATA	Drive Weight	0.22 lb (101 g)	
	Capacity	250 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	Synchronous	100 MB/s (Drive Capability)
		(maximum)	
	Seek Time	Single Track	3 ms
	(typical reads, including settling)	Average	13 ms
		Maximum	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	488,397,168	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

Technical Specifications

160-GB 5400 rpm SATA	Drive Weight	0.22 lb (101 g)
	Capacity	160 GB
	Height	0.37 in (9.5 mm)
	Width	2.75 in (70 mm)
	Interface	ATA-7 / SATA 1.0a
	Transfer Rate	Synchronous 100 MB/s (Drive Capability) (maximum)
	Seek Time	Single Track 3 ms
(typical reads, including settling)	Average	13ms
	Maximum	24 ms
	Rotational Speed	5400 rpm
	Logical Blocks	312,581,808
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]
	Features	ATA Security

120-GB 5400 rpm SATA	Drive Weight	0.22 lb (101 g)
	Capacity	120 GB
	Height	0.37 in (9.5 mm)
	Width	2.75 in (70 mm)
	Interface	ATA-7 / SATA 1.0a
	Transfer Rate	Synchronous 100 MB/s (Drive Capability) (maximum)
	Seek Time	Single Track 3 ms
(typical reads, including settling)	Average	13ms
	Maximum	24 ms
	Rotational Speed	5400 rpm
	Logical Blocks	234,441,648
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]
	Features	ATA Security

80-GB 5400 rpm SATA	Drive Weight	0.22 lb (101 g)
	Capacity	80 GB
	Height	0.37 in (9.5 mm)
	Width	2.75 in (70 mm)
	Interface	ATA-7 / SATA 1.0a
	Transfer Rate	Synchronous 100 MB/s (Drive Capability) (maximum)
	Seek Time	Single Track 3 ms
(typical reads, including settling)	Average	13 ms
	Maximum	24 ms
	Rotational Speed	5400 rpm
	Logical Blocks	156,301,488
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]
	Features	ATA Security

Technical Specifications

Removable Storage Drives

DVD-ROM Drive	Access Times	Random	<116 ms CD <125 ms DVD
		Max Data Transfer Rate	24X CD-ROM 3,600 KB/s 8X-DVD 10,800 KB/s
	Transfer Mode	Multiword DMA Mode 2	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW	
	Supported Media (write)	None	
	Max Media Capacity (read)	4.7 GB	
	Transport	Tray Loading	

DVD/CD-RW Combo Drive	Access Times	Random	<110 ms CD <130 ms DVD
		Max Data Transfer Rate	24X CD-ROM 3,600 KB/s 8X DVD 10,800 KB/s 24X CD-R 3,600 KB/s 24X CD-RW 3,600 KB/s
	Transfer Mode	Multiword DMA Mode 2	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW	
	Supported Media (write)	CD-R, CD-RW	
	Max Media Capacity (read)	8.5 GB	
	Max Media Capacity (write)	700 MB	
	Transport	Tray loading	

Technical Specifications

DVD+/-RW SuperMulti DL Drive	Access Times	Random	<175 ms CD <230 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X DVD	10,800 KB/s
		24X CD-R	3,600 KB/s
		16X CD-RW	2,400 KB/s
		8X DVD+R	10,800 KB/s
		4X DVD+RW	5,400 KB/s
		8X DVD-R	10,800 KB/s
		4X DVD-RW	5,400 KB/s
		2.4X DVD+R(9)	2,700 KB/s
		5X DVD-RAM	6,750 KB/s
	Transfer Mode	Multiword DMA Mode	
	Interface	EIDE	
Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM		
Supported Media (write)	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM		
Max Media Capacity (read)	8.5 GB		
Max Media Capacity (write)	8.5 GB		
Transport	Tray Loading		

DVD+/-RW SuperMulti DL LightScribe Drive	Access Times	Random	<175 ms CD <230 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X DVD	10,800 KB/s
		24X CD-R	3,600 KB/s
		16X CD-RW	2,400 KB/s
		8X DVD+R	10,800 KB/s
		4X DVD+RW	5,400 KB/s
		8X DVD-R	10,800 KB/s
		4X DVD-RW	5,400 KB/s
		2.4X DVD+R(9)	2,700 KB/s
		5X DVD-RAM	6,750 KB/s
	Transfer Mode	Multiword DMA Mode	
	Interface	EIDE	
Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM		
Supported Media (write)	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM, LightScribe		

Technical Specifications

Max Media Capacity (read)	8.5 GB
Max Media Capacity (write)	8.5 GB
Transport	Tray Loading

HP Fingerprint Sensor	Mobile Voltage Operation	3.0V–3.6V Single Supply
	Operating Temperature	32° – 158°F (0° – 70°C)
	Current Consumption @ 3.3V	Less than 70 mA peak imaging and scrolling Less than 25 mA hardware finger detection Advanced Power Management
	High-Rate Image Capture	Up to 240 image frames /sec
	ESD Resistance	IEC 61000-4-2 Level 4 (±15KV)
	Detection Matrix	192 x 16 Pixels 9.7 mm x 0.81 mm 500 ppi High-Resolution Images

Audio

Hardware	Implementation	ADI1981HD High Definition CODEC
	Touch-Sensitive Volume Controls	Volume up, volume down, and mute
	Full Duplex	Yes
	Sound Blaster Pro compatible	Yes
	Microphone In	Stereo
	Headphone/Line Out	Stereo
	Integrated Microphone	Yes

Audio Output Quality	Frequency Response	20 Hz – 20 kHz
	Signal to Noise Ratio	>85 dB
	Total Harmonic Distortion	0.01%
	Noise Floor	-110 dB
	Play/Record Sampling Rate(s)	8 kHz – 48kHz
	DAC	16, 20 or 24-bit
	ADC	16 or 20-bit

Integrated Stereo Speakers	Power Rating	2 Watts
	Impedance	4 Ohms

Technical Specifications

Communications

Integrated Broadcom NetLink Gigabit Ethernet Controller (10/100/1000 NIC)	Ethernet Features	<p>10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)</p> <p>100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)</p> <p>1000 Mbit/s operation (1000BASE-T; IEEE 802.3z and 802.3ab; IEEE 802.3 clauses 34-42)</p> <p>Auto-Negotiation (Automatic Speed Selection)</p> <p>Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s</p> <p>IEEE 802.1p QoS (Quality of Service) Support</p> <p>IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)</p>
	Power Management	<p>ACPI compliant -- multiple power modes</p> <p>Situation-sensitive features reduce power consumption</p>
	Performance Features	<p>TCP/IP/UDP Checksum Offload (configurable)</p>
	Manageability	<p>Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)</p> <p>PXE 2.1 Remote Boot</p> <p>Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))</p> <p>Comprehensive diagnostic and configuration software suite</p>
	Interface	<p>PCI Express x1</p>
	NIC Device Driver Name	<p>Broadcom NetLink Gigabit Ethernet</p>
	Drivers Available	<p>Microsoft Windows Vista</p> <p>Microsoft Windows XP</p>

V.92 56K Data/Fax Modem	Form Factor	<p>MDC 1.5 Daughtercard</p>
	Power Management Support	<p>APM Revision 1.2, ACPI</p>
	Approvals/Certifications	<p>UL, CSA, NEMKO, CCIB, Industry Canada, FCC Part 68, CTR21, FCC Part 15 Class B, Canadian ICES-003 Class B, C.I.S.P.R.22, Australian ACA, CE Mark, Other Countries</p>
	Data Mode Capabilities	<p>V.92 data</p> <p>V.8bis</p> <p>V.80</p> <p>V44, V.42bis, MNP5 (Compression)</p> <p>V.42 (LAPM, MNP2-4) (Error Correction)</p> <p>Optional symbol rates:</p> <p>2800, 3429</p> <p>Asymmetric Symbol rates</p> <p>Synchronous primary channel data signaling rates:</p> <p>3600, 31200</p> <p>Automatic rate re-negotiation</p> <p>V.34</p> <p>V.32bis</p> <p>V.32</p> <p>V.23</p> <p>V.22bis</p> <p>V.22</p>



Technical Specifications

	V.21 Bell 212A Bell 103J
Fax Mode Capabilities	TIA/EIA-578-B (Class 1) T.30, T.4 (Group 3) V.17 V.29 V.27ter V.21 Channel 2
Command Set	V.250 (Partial) TIA-602 Identification: +GMI, +GMM, +GMR Port control: +IPR, +ICF, +IFC, +ILRR Modulation: +MS, +MR, +MA Error control: +ES, +ER, +EB, +ESR, +ETBM Data compression: +DS, +DR V.251

HP ev2200 1xEV-DO Broadband Wireless Module	Band and Power Class	0 (North American Cellular) – Class III; 1 (North American PCS) – Class II
	Wireless Protocol Standards	CDMA 1x Release 0/A; IS-95A, IS-95B, IS-2000
	Wireless Parametric Standards	Meets or exceeds TIA/EIA IS-98-D
	Interoperability	CDG 22 (TIA/EIA/IS-95-A) CDG 53(TIA/EIA/IS-95-B) C.S0031 (TIA/EIA/IS-2000) CDG 64 (TIA/EIA/IS-2000) C.S0032 (TIA/EIA/IS-866)
	Frequency Band	Dual Band: 850 MHz (Cellular) and 1900 MHz (PCS)
	Data Rates (Packet Mode)	IS-856 rates up to 2.4 Mbps IS-2000 data rates up to 307.2 kbps
	Maximum Output Power	24dBm (+/-1)
	Power Consumption (maximum)	500mA
	Power Consumption, Sleep Mode	1.7mA – 3.5mA
	Power Management	USB selective suspend CDMA slotted mode sleep and dormant modes
	Antenna Type	High efficiency dual band antennae with spatial diversity, mounted in the display enclosure
	Form Factor	PCI-Express MiniCard
	Weight	0.35 oz (10 g)
	Dimensions (Length x Width x Thickness)	2.01 x 1.18 x 0.18 in (51 x 30 x 4.5 mm)
	Voltage, Operating	3.3v +/- 10%
	Temperature, Operating (from TIA/EIA/IS-98-D)	-22° to 140° F (-30° to 60° C) (full RF performance) -22° to 167° F (-30° to 75° C) (reduced RF performance)

Technical Specifications

Temperature, Non-operating, 96 hours (from MIL-STD 202 Method 108)	-40° to 185° F (-40° to 85° C)
Humidity, Non-operating	85% relative humidity for 48 hours @ 185° F (85° C) (non-condensing)
Configuration Utilities	Verizon Wireless VZAccess Manager
LED Activity	LED Off – Radio Off; Solid LED On – Radio On

HP hs2300 HSDPA Broadband Wireless Module	Frequency Bands and Power Class	850/1900/2100MHz WCDMA Power class 3 (+24dBm) 850MHz GSM/GPRS/EDGE 900MHz GSM/GPRS/EDGE, 1800MHz GSM/GPRS/EDGE 1900MHz GSM/GPRS/EDGE EDGE E2 power GPRS/EDGE Multislot Class 12 GPRS PCS/DCS power class 1 GSM power class 4
	Wireless Protocol Standards	GPRS/EDGE: 3GPP R99 GERAN P1 WCDMA Release 5 (R5) High-Speed Downlink Packet Access (HSDPA) 3.6Mbps GSM Phase 2+
	Wireless Parametric Standards	Complies with 3GPP specifications
	Additional Standards Compliance	FCC parts 15/22/24, CE, Microsoft WHQL, R&TTE directive 1999/5/EC (health, safety, EMC, spectrum), GCF-CC (Module), European Union Directive 2002/95/EC (restrictions of the use of certain Hazardous Substances (RoHS) in electronic equipment), Infrastructure Interoperability Testing (IOT)
	Data Rates (Packet Mode)	Designed maximum data rate: EDGE 118 kbps UL / 236 kbps DL UMTS 384 kbps UL / 384 kbps DL HSDPA 384 kbps UL / 3.6 Mbps DL
	Chipset and Module	Qualcomm MSM6280 chipset; Sierra Wireless MC8775 module
	Maximum Output Power	32 dBm (+/-2) GSM/EDGE GMSK mode
	Power Consumption (maximum)	800mA
	Power Consumption, Sleep Mode	4 – 8mA
	Power Management	USB Selective Suspend sleep and standby mode
Antenna Type	High efficiency 5- band antennae, mounted in the display enclosure	
Form Factor	PCI-Express MiniCard	
Weight	0.35 oz (10 g)	
Dimensions (Length x Width x Thickness)	2.01 x 1.18 x 0.18 in (51 x 30 x 4.5 mm)	
Voltage, Operating	3.3v +/- 10%	

Technical Specifications

Temperature, Operating	-22° to 140° F (-30° to 60° C) (full RF performance) -22° to 167° F (-30° to 75° C) (reduced RF performance)
Temperature, Non-operating, 96 hours (from MIL-STD 202 Method 108)	-40° to 185° F (-40° to 85° C)
Humidity, Non-operating	85% relative humidity for 48 hours @ 185° F (85° C) (non-condensing)
LED Activity	LED Off – Radio Off; Solid LED On – Radio On
Configuration Utilities	Varies per country and mobile network operator

Broadcom 4311AG 802.11a/b/g WiFi Adapter

Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g
Interoperability	Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows 2000 and XP (details at http://www.hp.com/go/notebooks/WLAN)
Frequency Band	2.4 GHz and 5 GHz
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
Security¹	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST. Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).
Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power (for CKK) ²	17.5 dBm
Output Power (for OFDM; power varies by data rate) ²	15 dBm
Power Consumption	Transmit: 2.0 W (max) Receive: 1.5 W (max) Idle mode ³ : 390 mW (nominal) Sleep mode: 20 mW (max)
Power Management	ACPI compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	54 Mbps: -72 dBm, 11 Mbps: -88 dBm, 1 Mbps: -97 dBm
Antenna type	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure

Technical Specifications

Range	802.11 a – Typical (@6 Mbps)	600 feet – Outdoor Open Area 150 feet – Indoor, Office environment
	802.11 b – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
Form Factor	PCI-Express MiniCard	
Weight	0.026 lb (12 g)	
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
Operating Voltage	3.3v +/- 10%	
Temperature	Operating	32° to 176° F (0° to 80° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
Configuration Utility⁵	Microsoft Windows 2000 or XP Choice of Configuration Utility: <ul style="list-style-type: none"> • Microsoft Windows XP Wireless Network Connection Manager • Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support) 	
	Microsoft Windows Vista <ul style="list-style-type: none"> • Microsoft Windows Vista Wireless Network Connection Manager 	
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON	
	<ol style="list-style-type: none"> 1. Check latest software/driver release for updates on supported security features. 2. Maximum output power may vary by country according to local regulations. 3. In Power Save Polling mode. 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation). 5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows 2000 or XP. WLAN may also be compatible with certain third-party software supplicants. 	

Broadcom 4311BG 802.11b/g WiFi Adapter	Wireless LAN Standards	IEEE 802.11b IEEE 802.11g
	Interoperability	Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows 2000 and XP (details at http://www.hp.com/go/notebooks/WLAN)
	Frequency Band	2.4 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
	Security¹	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST.

Support for Cisco Security Features (proven compatibility with Cisco



Technical Specifications

	Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).	
Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.	
Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK	
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)	
Roaming	IEEE 802.11 compliant roaming between access points	
Output Power (for CKK) ²	17.5 dBm	
Output Power (for OFDM; power varies by data rate) ²	15 dBm	
Power Consumption	Transmit: 2.0 W (max) Receive: 1.5 W (max) Idle mode ³ : 390 mW (nominal) Sleep mode: 20 mW (max)	
Power Management	ACPI compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity ⁴	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm	
Antenna type	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure	
Range	802.11 b – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
Form Factor	PCI-Express MiniCard	
Weight	0.026 lb (12 g)	
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
Operating Voltage	3.3v +/- 10%	
Temperature	Operating	32° to 176° F (0° to 80° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)

Technical Specifications

Configuration Utility⁵	<p>Microsoft Windows 2000 or XP Choice of Configuration Utility:</p> <ul style="list-style-type: none"> • Microsoft Windows XP Wireless Network Connection Manager • Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support) <p>Microsoft Windows Vista</p> <ul style="list-style-type: none"> • Microsoft Windows Vista Wireless Network Connection Manager
LED Activity	<p>LED Off – Radio OFF; Solid LED On – Radio ON</p> <ol style="list-style-type: none"> 1. Check latest software/driver release for updates on supported security features. 2. Maximum output power may vary by country according to local regulations. 3. In Power Save Polling mode. 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation). 5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows 2000 or XP. WLAN may also be compatible with certain third-party software supplicants.

Broadcom 4321AGN 802.11a/b/g/draft-n WiFi Standards Adapter	Wireless LAN	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n (draft)
	Interoperability	Wi-Fi certified (802.11abg only) Cisco Compatible Extensions Program compliant (802.11abg only) with Microsoft Windows 2000 and XP (details at http://www.hp.com/go/notebooks/WLAN) Tested with wireless access points from several major manufacturers (details at http://www.hp.com/go/notebooks/WLAN/draft-n)
	Frequency Band	2.4 GHz and 5 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n (draft): 6, 6.5, 9, 12, 13, 13.5, 18, 19.5, 24, 26, 27, 36, 39, 40.5, 48, 52, 54, 58.5, 65, 78, 81, 104, 108, 117, 121.5, 130, 135, 162, 216, 243, 270 Mbps
	Frequency Support	20 MHz: 2.4 GHz and 5 GHz bands 40 MHz: 5 GHz band only
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
	Security¹	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST. Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4) with Microsoft Windows 2000 and XP only.
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)

Technical Specifications

Roaming	IEEE 802.11 compliant roaming between access points	
Output Power (for CKK) ²	17 dBm	
Output Power (for OFDM; power varies by data rate) ²	15 dBm	
Power Consumption	Idle associated: 300 mW Idle unassociated: 150 mW Transmit/Receive 20 MHz channel: 2.6 W (max) Transmit/Receive 40 MHz channel: 3.3 W (max)	
Power Management	ACPI compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity ³	270 Mbps: -66dBm, 162 Mbps: -72 dBm, 54 Mbps: -72 dBm, 11 Mbps: -85 dBm , 1 Mbps: -94 dBm	
Antenna type	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure	
Range	802.11 a – Typical (@6 Mbps)	600 feet – Outdoor Open Area 150 feet – Indoor, Office environment
	802.11 b – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
Form Factor	PCI-Express MiniCard	
Weight	0.026 lb (12 g)	
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
Operating Voltage	3.3v +/- 10%	
Temperature	Operating	14° to 149° F (–10° to 65° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
Configuration Utility ⁴	Microsoft Windows 2000 or XP Choice of Configuration Utility: <ul style="list-style-type: none"> ● Microsoft Windows XP Wireless Network Connection Manager ● Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support) Microsoft Windows Vista <ul style="list-style-type: none"> ● Microsoft Windows Vista Wireless Network Connection Manager 	
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON	
	<ol style="list-style-type: none"> 1. Check latest software/driver release for updates on supported security features. 2. Maximum output power may vary by country according to local regulations. 3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation). 4. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows 2000 or XP. WLAN may also be compatible with certain third-party software supplicants. 	

Technical Specifications

HP Integrated Module with Bluetooth Wireless Technology	Bluetooth Specification	2.0 Compliant
	Dimensions	1.02 x 0.55 x 0.22 in (26 x 14 x 5.7 mm)
	Frequency Band	2402 to 2480 MHz
	Number of Available Channels	79 (1 MHz) available channels
	Data Rates and Throughput	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric
	Transmit Power	-6 dBm to 4 dBm (Bluetooth Class II)
	Receiver Sensitivity	Better than -80 dBm at 0.1 % raw bit error rate
	Power Consumption	Peak (Tx) 264 mW Peak (Rx) 231 mW Sleep <1 mW
	Antenna	Internally integrated within module
	Range	Up 33 ft (10 m)
	Electrical Interface	USB 2.0 compliant Microsoft Windows Plug and Play compliant
	OS Support	Genuine Windows Vista Genuine Windows XP Genuine Windows 2000
	Bluetooth Software Supported	Broadcom Bluetooth for Windows Microsoft Windows XP Bluetooth Software
	Link Topology	Point to Point, Multipoint Pico Nets up to 7 slaves
	Security	Full support of Bluetooth Security Provisions
	Power Management	Microsoft Windows ACPI, and USB Bus Support Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
	Certifications	All necessary regulatory approvals for supported countries, including: FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
	Temperature	Operating -4° to 158° F (-20° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
	Humidity	Operating 10% to 90% Non-operating 5% to 95%
	Altitude	Operating 15,000 ft (4,572 m) Non-operating 40,000 ft (12,192 m)
	Bluetooth Profiles Supported	(with Bluetooth for Windows 4.0 software) Serial Port Profile (SPP)* Dial-Up Networking (DUN)* Generic Object Exchange Profile (GOEP) Object Push Profile (OPP)* File Transfer Profile (FTP)

Technical Specifications

Synchronization Profile (SYNC)
 Hard Copy Cable Replacement (HCRP)*
 Personal Area Networking Profile (PAN)*
 Human Interface Device Profile (HID)*
 FAX Profile (FAX)
 Basic Imaging Profile (BIP)
 Headset Profile (HSP)
 Hands Free Profile (HFP)
 Advanced Audio Distribution Profile (A2DP)

* indicates the profile is also supported by Microsoft Windows XP SP2

Environmental Data

Eco-Label Certifications

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- ENERGY STAR 4.0
- US Federal Energy Management Program (FEMP)
- Taiwan Green Mark
- China Energy Conservation Program
- IT ECO declaration
- Korean Eco Label

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data is based on a "Typically Configured Notebook"

Energy Consumption

	115 VAC	230 VAC	100 VAC
Normal Operation	13.76 W	13.24 W	13.65 W
Sleep (Energy Star low power mode)	1.16 W	1.38 W	1.15 W
Off	1.2 W	1.4 W	1.2 W

Heat Dissipation*

	115 VAC	230 VAC	100 VAC
Normal Operation	46.949 BTU/hr	45.174 BTU/hr	45.823 BTU/hr
Sleep	3.957 BTU/hr	4.708 BTU/hr	3.923 BTU/hr
Off	4.094 BTU/hr	4.776 BTU/hr	4.094 BTU/hr

* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

This product is in compliance with US executive order 13221, WOL (wake on LAN) disabled.

Declared Noise Emissions

(in accordance with ISO 7779 and ISO 9296)

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Idle	3.25	21.9
Operating mode (HDD)	3.2	23.2

Batteries

This product complies with ISO standards:

- EU Directive 91/ 157/ EEC
- EU Directive 93/ 86/ EEC
- EU Directive 98/ 101/ EEC

Batteries used in the product do not contain:



Technical Specifications

- Mercury greater than 5ppm by weight
- Cadmium greater than 10ppm by weight
- Lead greater than 4000 ppm by weight.

The battery type and chemistry used in the product is:

CR2032 (coin cell), Lithium

6 cell rechargeable Lithium-Ion battery; optional 8 cell Lithium-Ion battery available

Additional information:

This product is in compliance with the EU Restrictions of Hazardous Substances (RoHS) Directive – 2002/95/EC.

This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.

Keyboard complies with ISO standard: ISO 9995, EN 29241-4, and ISO/IEC 15412

Input devices of this product comply with ISO 9241, part 9.

Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.

This product contains 0% recycled materials (by wt.)

This product is greater than 95% recyclable when properly disposed of at end of life.

Packaging Materials

- Corrugated / Paper – 2.41 lb (1094 g)
- EPE Foam – 0.112 lb (51 g)
- LDPE Bag – 0.011 lb (5 g)
- The corrugated paper packaging materials contains at least 40% recycled content.

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (for reference of these limits please refer to the HP General Specification of the Environment

(http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):

- Asbestos

Technical Specifications

- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

End-of-life Management and Recycling

HP offers our customers several other options for handling their aging computers while also minimizing the impact on the environment—including product trade-in and leasing services—in addition to recycling services.

Please go to: <http://www.hp.com/recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment: Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Environment website

<http://www.hp.com/environment>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

Copyright © 2008 Hewlett-Packard Development Company, L.P.

All rights reserved. Microsoft, Windows, Windows Vista and Windows XP are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Turion and Sempron are registered trademarks or trademarks of AMD Corporation in the U.S. and/or other countries. Bluetooth is a registered trademark of Bluetooth SIG, Inc., in the U.S. and other countries. All other product names mentioned herein may be trademarks of their respective companies.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

